



Functional information for outbound Advance Ship Notice (ASN)
EDIFACT - DESADV
ANSI X12 - 856

Micron has created a standard electronic Advance Ship Notice (ASN) document format. This standard format includes specific details from the purchase order that was received by the Micron SAP system, as well as shipping specific data. The use of this standardized format will allow faster implementations with our customers, and a more accurate exchange of data between our systems. Above and beyond the standard from the original order (PO number, material, order quantity, ship date, price), Micron also includes the following in our ASN transmissions:

Shipment ID: This will include a unique shipment identifier (Delivery Note Number) for each shipment included in the transmission.

Ship Date: The Ship date is the date that the product physically left a Micron facility.

Reference Numbers: Additional reference numbers (Waybill Number, Bill of Lading Number, Packing List Number, etc.) can be included in the transmission if required.

Name and address information (Ship-From, Ship-to: The Ship-From and Ship-to information will reference the Ship-From and ship-to data that were on the delivery at the time of shipment.

Carrier Details: Indicates the shipping method and carrier information for the shipment.

Packing information: The ASN will include a structured Order, Shipment, Pack and Item layout that will indicate how the product was packaged, including showing inner and outer container information.

856 Ship Notice/Manifest

Functional Group ID=**SH**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Ship Notice/Manifest Transaction Set (856) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to list the contents of a shipment of goods as well as additional information relating to the shipment, such as order information, product description, physical characteristics, type of packaging, marking, carrier information, and configuration of goods within the transportation equipment. The transaction set enables the sender to describe the contents and configuration of a shipment in various levels of detail and provides an ordered flexibility to convey information. The sender of this transaction is the organization responsible for detailing and communicating the contents of a shipment, or shipments, to one or more receivers of the transaction set. The receiver of this transaction set can be any organization having an interest in the contents of a shipment or information about the contents of a shipment.

Heading:

	<u>Pos.</u> <u>No.</u>	<u>Seg.</u> <u>ID</u>	<u>Name</u>	<u>Req.</u> <u>Des.</u>	<u>Max.Use</u>	<u>Loop</u> <u>Repeat</u>
M	010	ST	Transaction Set Header	M	1	
M	020	BSN	Beginning Segment for Ship Notice	M	1	
	040	DTM	Date/Time Reference	O	10	

Detail:

	<u>Pos.</u> <u>No.</u>	<u>Seg.</u> <u>ID</u>	<u>Name</u>	<u>Req.</u> <u>Des.</u>	<u>Max.Use</u>	<u>Loop</u> <u>Repeat</u>
			LOOP ID - HL			200000
M	010	HL	Hierarchical Level	M	1	
	020	LIN	Item Identification	O	1	
	030	SN1	Item Detail (Shipment)	O	1	
	050	PRF	Purchase Order Reference	O	1	
	060	PO4	Item Physical Details	O	1	
	110	TD1	Carrier Details (Quantity and Weight)	O	20	
	120	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12	
	150	REF	Reference Identification	O	>1	
			LOOP ID - N1			200
	220	N1	Name	O	1	
	240	N3	Address Information	O	2	
	250	N4	Geographic Location	O	1	

Summary:

<u>Pos.</u> <u>No.</u>	<u>Seg.</u> <u>ID</u>	<u>Name</u>	<u>Req.</u> <u>Des.</u>	<u>Max.Use</u>	<u>Loop</u> <u>Repeat</u>
---------------------------	--------------------------	-------------	----------------------------	----------------	------------------------------

	010	CTT	Transaction Totals	O	1
M	020	SE	Transaction Set Trailer	M	1

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Business Rules: Variable Name: STST

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set 856 Ship Notice/Manifest	M ID 3/3
M	ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Segment: **BSN** Beginning Segment for Ship Notice
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	BSN01	353	Transaction Set Purpose Code Code identifying purpose of transaction set 00 Original	M ID 2/2
M	BSN02	396	Shipment Identification A unique control number assigned by the original shipper to identify a specific shipment	M AN 2/30
M	BSN03	373	Date Date expressed as CCYYMMDD	M DT 8/8
M	BSN04	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	M TM 4/8

Segment: **DTM** Date/Time Reference
Position: 040
Loop:
Level: Heading
Usage: Optional
Max Use: 10
Purpose: To specify pertinent dates and times

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	DTM01	374	Date/Time Qualifier Code specifying type of date or time, or both date and time 011 Shipped	M ID 3/3
	DTM02	373	Date Date expressed as CCYYMMDD	X DT 8/8
	DTM03	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	X TM 4/8

Segment: **HL** Hierarchical Level
Position: 010
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	HL01	628	Hierarchical ID Number	M AN 1/12
			A unique number assigned by the sender to identify a particular data segment in a hierarchical structure	
	HL02	734	Hierarchical Parent ID Number	O AN 1/12
			Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to	
M	HL03	735	Hierarchical Level Code	M ID 1/2
			Code defining the characteristic of a level in a hierarchical structure	
		I	Item	
		O	Order	
		P	Pack	
		S	Shipment	
	HL04	736	Hierarchical Child Code	O ID 1/1
			Code indicating if there are hierarchical child data segments subordinate to the level being described	
		0	No Subordinate HL Segment in This Hierarchical Structure.	
		1	Additional Subordinate HL Data Segment in This Hierarchical Structure.	

Segment: **LIN** Item Identification
Position: 020
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify basic item identification data

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
	LIN01	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20
M	LIN02	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) VP Vendor's (Seller's) Part Number	M ID 2/2
M	LIN03	234	Product/Service ID Identifying number for a product or service	M AN 1/48
	LIN04	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) BP Buyer's Part Number	X ID 2/2
	LIN05	234	Product/Service ID Identifying number for a product or service	X AN 1/48
	LIN06	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) UP U.P.C. Consumer Package Code (1-5-5-1)	X ID 2/2
	LIN07	234	Product/Service ID Identifying number for a product or service	X AN 1/48

Segment: **SN1** Item Detail (Shipment)
Position: 030
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify line-item detail relative to shipment

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
	SN101	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20
M	SN102	382	Number of Units Shipped Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set	M R 1/10
M	SN103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken EA Each	M ID 2/2

Segment: **PRF** Purchase Order Reference
Position: 050
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To provide reference to a specific purchase order

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PRF01	324	Purchase Order Number Identifying number for Purchase Order assigned by the orderer/purchaser	M AN 1/22
	PRF04	373	Date Date expressed as CCYYMMDD	O DT 8/8
	PRF07	92	Purchase Order Type Code Code specifying the type of Purchase Order BY Buying	O ID 2/2

Segment: **PO4** Item Physical Details
Position: 060
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify the physical qualities, packaging, weights, and dimensions relating to the item

Data Element Summary			
Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
PO401	356	Pack	O N0 1/6
		The number of inner containers, or number of eaches if there are no inner containers, per outer container	
PO403	355	Unit or Basis for Measurement Code	X ID 2/2
		Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
		KG	Kilogram
		LB	Pound
PO405	187	Weight Qualifier	O ID 1/2
		Code defining the type of weight	
		G	Gross Weight
PO406	384	Gross Weight per Pack	X R 1/9
		Numeric value of gross weight per pack	
PO407	355	Unit or Basis for Measurement Code	X ID 2/2
		Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
		KG	Kilogram
		LB	Pound

Segment: **TD1** Carrier Details (Quantity and Weight)
Position: 110
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 20
Purpose: To specify the transportation details relative to commodity, weight, and quantity

Data Element Summary

Ref. <u>Des.</u>	Data <u>Element</u>	<u>Name</u>	<u>Attributes</u>
TD101	103	Packaging Code Code identifying the type of packaging; Part 1: Packaging Form, Part 2: Packaging Material; if the Data Element is used, then Part 1 is always required CTN Carton	O AN 3/5
TD102	80	Lading Quantity Number of units (pieces) of the lading commodity	X N0 1/7

Segment: **TD5** **Carrier Details (Routing Sequence/Transit Time)**
Position: 120
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 12
Purpose: To specify the carrier and sequence of routing and provide transit time information

Data Element Summary			
Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
TD501	133	Routing Sequence Code	O ID 1/2
		Code describing the relationship of a carrier to a specific shipment movement	
		O Origin Carrier (Air, Motor, or Ocean)	
TD502	66	Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)	
		2 Standard Carrier Alpha Code (SCAC)	
TD503	67	Identification Code	X AN 2/80
		Code identifying a party or other code	
TD504	91	Transportation Method/Type Code	X ID 1/2
		Code specifying the method or type of transportation for the shipment	
		A Air	
		M Motor (Common Carrier)	
		ZZ Mutually defined	
TD505	387	Routing	X AN 1/35
		Free-form description of the routing or requested routing for shipment, or the originating carrier's identity	

Segment: **REF** **Reference Identification**
Position: 150
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	REF01	128	Reference Identification Qualifier	M ID 2/3
			Code qualifying the Reference Identification	
			AW Air Waybill Number	
			BM Bill of Lading Number	
			DO Delivery Order Number	
			LS Bar-Coded Serial Number	
			PK Packing List Number	
	REF02	127	Reference Identification	X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	

Segment: **N1** Name
Position: 220
Loop: N1 Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code

Data Element Summary				
	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
M	N101	98	Entity Identifier Code	M ID 2/3
			Code identifying an organizational entity, a physical location, property or an individual	
			SF Ship From	
			ST Ship To	
	N102	93	Name	X AN 1/60
			Free-form name	
	N103	66	Identification Code Qualifier	X ID 1/2
			Code designating the system/method of code structure used for Identification Code (67)	
			91 Assigned by Seller or Seller's Agent	
			92 Assigned by Buyer or Buyer's Agent	
	N104	67	Identification Code	X AN 2/80
			Code identifying a party or other code	

Segment: **N3** Address Information
Position: 240
Loop: N1 Optional
Level: Detail
Usage: Optional
Max Use: 2
Purpose: To specify the location of the named party

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N301	166	Address Information Address information	M AN 1/55
	N302	166	Address Information Address information	O AN 1/55

Segment: **N4** Geographic Location
Position: 250
Loop: N1 Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify the geographic place of the named party

Data Element Summary			
Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
N401	19	City Name Free-form text for city name	O AN 2/30
N402	156	State or Province Code Code (Standard State/Province) as defined by appropriate government agency	O ID 2/2
N403	116	Postal Code Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O ID 3/15
N404	26	Country Code Code identifying the country	O ID 2/3

Segment: **CTT** Transaction Totals
Position: 010
Loop:
Level: Summary
Usage: Optional
Max Use: 1
Purpose: To transmit a hash total for a specific element in the transaction set

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	CTT01	354	Number of Line Items	M N0 1/6
			Total number of line items in the transaction set	
	CTT02	347	Hash Total	O R 1/10
			Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element.	

Example:

-.0018 First occurrence of value being hashed.

.18 Second occurrence of value being hashed.

1.8 Third occurrence of value being hashed.

18.01 Fourth occurrence of value being hashed.

1855 Hash total prior to truncation.

855 Hash total after truncation to three-digit field.

Segment: **SE** Transaction Set Trailer
Position: 020
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
M	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

DESADV Despatch Advice Message

Introduction:

A message specifying details for goods despatched or ready for despatch under agreed conditions. The United Nations Despatch Advice Message serves both as a specification for Delivery Despatch Advice and also as a Returns Despatch Advice message. Throughout this document, the reference to 'Despatch Advice' may be interpreted as conveying the wider meaning of 'Delivery Despatch Advice/Returns Despatch Advice'.

Heading Section:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Group Repeat</u>
M	0010	UNH	Message Header	M	1	
M	0020	BGM	Beginning of Message	M	1	
	0030	DTM	Date/Time/Period	C	10	
	0070		Segment Group 1: RFF	C		10
M	0080	RFF	Reference	M	1	
	0100		Segment Group 2: NAD	C		10
M	0110	NAD	Name and Address	M	1	

Detail Section:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Group Repeat</u>
	0370		Segment Group 10: CPS-SG15	C		9999
M	0380	CPS	Consignment Packing Sequence	M	1	
	0550		Segment Group 15: LIN-PIA-QTY-SG16	C		9999
M	0560	LIN	Line Item	M	1	
	0570	PIA	Additional Product Id	C	10	
	0600	QTY	Quantity	C	10	
	0710		Segment Group 16: RFF	C		99
M	0720	RFF	Reference	M	1	

Summary Section:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Group Repeat</u>
M	1040	UNT	Message Trailer	M	1	

Segment: **UNH** Message Header
Position: 0010
Group:
Level: 0
Usage: Mandatory
Max Use: 1
Purpose: A service segment starting and uniquely identifying a message. The message type code for the Despatch advice message is DESADV.
 Note: Despatch advice messages conforming to this document must contain the following data in segment UNH, composite S009:
 Data element 0065 DESADV 0052 D 0054 97A 0051 UN
Business Rules: Variable Name: UNH1

Data Element Summary

	<u>Data Element</u>	<u>Component</u>		<u>Attributes</u>
		<u>Element</u>	<u>Name</u>	
M	0062		MESSAGE REFERENCE NUMBER	M an..14
			Unique message reference assigned by the sender.	
M	S009		MESSAGE IDENTIFIER	M
			Identification of the type, version etc. of the message being interchanged.	
M		0065	Message type identifier	M an..6
			Code identifying a type of message and assigned by its controlling agency.	
		DESADV	Despatch advice message	
			A code to identify the despatch advice message.	
M		0052	Message type version number	M an..3
			Version number of a message type.	
		D	Draft version/UN/EDIFACT Directory	
			Message approved and issued as a draft message (Valid for directories published after March 1993 and prior to March 1997). Message approved as a standard message (Valid for directories published after March 1997).	
M		0054	Message type release number	M an..3
			Release number within the current message type version number (0052).	
		97A	Release 1997 - A	
			Message approved and issued in the first 1997 release of the UNTDID (United Nations Trade Data Interchange Directory).	
M		0051	Controlling agency	M an..2
			Code identifying the agency controlling the specification, maintenance and publication of the message type.	
		UN	UN/ECE/TRADE/WP.4	

United Nations Economic UN Economic Commission
for Europe (UN/ECE), Committee on the development
of trade (TRADE), Working Party on facilitation of
international trade procedures (WP.4).

Segment: **BGM** Beginning of Message
Position: 0020
Group:
Level: 0
Usage: Mandatory
Max Use: 1
Purpose: A segment for unique identification of the Despatch Advice document, by means of its name and its number.

Data Element Summary

<u>Data Element</u>	<u>Component Element</u>	<u>Name</u>	<u>Attributes</u>
C002		DOCUMENT/MESSAGE NAME	C
		Identification of a type of document/message by code or name. Code preferred.	
	1001	Document/message name, coded	C an..3
		Document/message identifier expressed in code.	
	351	Despatch advice	
		Document/message by means of which the seller or consignor informs the consignee about the despatch of goods.	
C106		DOCUMENT/MESSAGE IDENTIFICATION	C
		Identification of a document/message by its number and eventually its version or revision.	
	1004	Document/message number	C an..35
		Reference number assigned to the document/message by the issuer.	
1225		MESSAGE FUNCTION, CODED	C an..3
		Code indicating the function of the message.	
	9	Original	
		Initial transmission related to a given transaction.	

Segment: **DTM** Date/Time/Period
Position: 0030
Group:
Level: 1
Usage: Conditional (Optional)
Max Use: 10
Purpose: Date/time/period related to the whole message. The DTM segment must be specified at least once to identify the Despatch Advice date.

Data Element Summary

	<u>Data Element</u>	<u>Component Element</u>	<u>Name</u>	<u>Attributes</u>
M	C507		DATE/TIME/PERIOD	M
			Date and/or time, or period relevant to the specified date/time/period type.	
M		2005	Date/time/period qualifier	M an..3
			Code giving specific meaning to a date, time or period.	
		11	Despatch date and or time (2170) Date/time on which the goods are or are expected to be despatched or shipped.	
		2380	Date/time/period	C an..35
			The value of a date, a date and time, a time or of a period in a specified representation.	
		2379	Date/time/period format qualifier	C an..3
			Specification of the representation of a date, a date and time or of a period.	
		102	CCYYMMDD Calendar date: C = Century ; Y = Year ; M = Month ; D = Day.	

Group: **RFF** Segment Group 1: Reference
Position: 0070
Group:
Level: 1
Usage: Conditional (Optional)
Max Use: 10
Purpose: A group of segments giving references where necessary, their dates relating to the whole message, e.g. contract number.

Segment Summary						
	Pos.	Seg.		Req.	Max.	Group:
	<u>No.</u>	<u>ID</u>	<u>Name</u>	<u>Des.</u>	<u>Use</u>	<u>Repeat</u>
M	0080	RFF	Reference	M	1	

Segment: **RFF** Reference
Position: 0080 (Trigger Segment)
Group: Segment Group 1 (Reference) Conditional (Optional)
Level: 1
Usage: Mandatory
Max Use: 1
Purpose: A segment for referencing documents relating to the whole despatch advice message, e.g. purchase orders, delivery instructions, import/export license.

Data Element Summary

	<u>Data Element</u>	<u>Component Element</u>	<u>Name</u>	<u>Attributes</u>
M	C506		REFERENCE Identification of a reference.	M
M		1153	Reference qualifier Code giving specific meaning to a reference segment or a reference number. AWB Air waybill number Reference number assigned to an air waybill, see: 1001 = 740.	M an..3
		1154	Reference number Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier.	C an..35

Group: **NAD** Segment Group 2: Name and Address
Position: 0100
Group:
Level: 1
Usage: Conditional (Optional)
Max Use: 10
Purpose: A group of segments identifying names, addresses, locations, and required supporting documents relevant to the whole Despatch Advice.

Segment Summary						
	Pos.	Seg.		Req.	Max.	Group:
	<u>No.</u>	<u>ID</u>	<u>Name</u>	<u>Des.</u>	<u>Use</u>	<u>Repeat</u>
M	0110	NAD	Name and Address	M	1	

Segment: **NAD** Name and Address

Position: 0110 (Trigger Segment)

Group: Segment Group 2 (Name and Address) Conditional (Optional)

Level: 1

Usage: Mandatory

Max Use: 1

Purpose: A segment for identifying names, addresses, and their functions relevant to the whole Despatch Advice. Identification of the parties involved is recommended for the Despatch Advice message, and is to be given in the NAD segment. It is recommended that where possible, only the coded form of the party ID should be specified, e.g. the buyer and seller are known to each other, thus only the coded ID is required. The consignee or delivery address may vary and would have to be clearly specified, preferably in structured format.

Data Element Summary				
	Data Element	Component Element	Name	Attributes
M	3035		PARTY QUALIFIER	M an..3
			Code giving specific meaning to a party.	
		SF	Ship from	
			Identification of the party from where goods will be or have been shipped.	
		ST	Ship to	
M	C082		Identification of the party to where goods will be or have been shipped.	
		SU	Supplier	
			(3280) Party which manufactures or otherwise has possession of goods, and consigns or makes them available in trade.	
		UD	Ultimate customer	
			The final recipient of goods.	
M	3039		PARTY IDENTIFICATION DETAILS	C
			Identification of a transaction party by code.	
			Party id. identification	M an..35
			Code identifying a party involved in a transaction.	
		3055	Code list responsible agency, coded	C an..3
M	C080		Code identifying the agency responsible for a code list.	
		91	Assigned by seller or seller's agent	
		92	Assigned by buyer or buyer's agent	
			PARTY NAME	C
			Identification of a transaction party by name, one to five lines. Party name may be formatted.	
M	3036		Party name	M an..35

	Name of a party involved in a transaction.	
3164	CITY NAME	C an..35
	Name of a city (a town, a village) for addressing purposes.	
3251	POSTCODE IDENTIFICATION	C an..9
	Code defining postal zones or addresses.	
3207	COUNTRY, CODED	C an..3
	Identification of the name of a country or other geographical entity as specified in ISO 3166.	

Group: **CPS** Segment Group 10: Consignment Packing Sequence
Position: 0370
Group:
Level: 1
Usage: Conditional (Optional)
Max Use: 9999
Purpose: A group of segments providing details of all package levels and of the individual despatched items contained in the consignment. This segment group provides the capability to give the hierarchical packing relationships. The group defines a logical top-down order structure. The lowest level package information of the hierarchy is followed by the detail product information.

Segment Summary

	Pos.	Seg.		Req.	Max.	Group:
	<u>No.</u>	<u>ID</u>	<u>Name</u>	<u>Des.</u>	<u>Use</u>	<u>Repeat</u>
M	0380	CPS	Consignment Packing Sequence	M	1	
	0550		Segment Group 15: Line Item	C		9999

Segment: **CPS** **Consignment Packing Sequence**
Position: 0380 (Trigger Segment)
Group: Segment Group 10 (Consignment Packing Sequence) Conditional (Optional)
Level: 1
Usage: Mandatory
Max Use: 1
Purpose: A segment identifying the sequence in which packing of the consignment occurs, e.g. boxes loaded onto a pallet.

Data Element Summary

Data Component			
<u>Element</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	7164	HIERARCHICAL ID. NUMBER	M an..12
		A unique number assigned by the sender to identify a level within a hierarchical structure.	

Group: **LIN** Segment Group 15: Line Item
Position: 0550
Group: Segment Group 10 (Consignment Packing Sequence) Conditional (Optional)
Level: 2
Usage: Conditional (Optional)
Max Use: 9999
Purpose: A group of segments providing details of the individual despatched items.

Segment Summary						
	Pos.	Seg.		Req.	Max.	Group:
	<u>No.</u>	<u>ID</u>	<u>Name</u>	<u>Des.</u>	<u>Use</u>	<u>Repeat</u>
M	0560	LIN	Line Item	M	1	
	0570	PIA	Additional Product Id	C	10	
	0600	QTY	Quantity	C	10	
	0710		Segment Group 16: Reference	C		99

Segment: **LIN** Line Item
Position: 0560 (Trigger Segment)
Group: Segment Group 15 (Line Item) Conditional (Optional)
Level: 2
Usage: Mandatory
Max Use: 1
Purpose: A segment identifying the product being despatched.
 All other segments in the detail section following the LIN segment refer to that line item.

Data Element Summary

Data	Component		
<u>Element</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
1082		LINE ITEM NUMBER	C an..6
		Serial number designating each separate item within a series of articles.	
C212		ITEM NUMBER IDENTIFICATION	C
		Goods identification for a specified source.	
	7140	Item number	C an..35
		A number allocated to a group or item.	
	7143	Item number type, coded	C an..3
		Identification of the type of item number.	
		BP Buyer's part number	
		Reference number assigned by the buyer to identify an article.	
	3055	Code list responsible agency, coded	C an..3
		Code identifying the agency responsible for a code list.	
		92 Assigned by buyer or buyer's agent	

Segment: **PIA** Additional Product Id
Position: 0570
Group: Segment Group 15 (Line Item) Conditional (Optional)
Level: 3
Usage: Conditional (Optional)
Max Use: 10
Purpose: A segment providing additional product identification.

Data Element Summary

	<u>Data Element</u>	<u>Component Element</u>	<u>Name</u>	<u>Attributes</u>
M	4347		PRODUCT ID. FUNCTION QUALIFIER Indication of the function of the product code. 1 Additional identification Information which specifies and qualifies product identifications.	M an..3
M	C212		ITEM NUMBER IDENTIFICATION Goods identification for a specified source.	M
		7140	Item number A number allocated to a group or item.	C an..35
		7143	Item number type, coded Identification of the type of item number. VP Vendor's (seller's) part number Reference number assigned by a vendor/seller identifying an article.	C an..3
		3055	Code list responsible agency, coded Code identifying the agency responsible for a code list. 91 Assigned by seller or seller's agent	C an..3

Segment: **QTY** Quantity
Position: 0600
Group: Segment Group 15 (Line Item) Conditional (Optional)
Level: 3
Usage: Conditional (Optional)
Max Use: 10
Purpose: A segment to give quantity information concerning the product.

Data Element Summary

	Data Component		<u>Attributes</u>
	<u>Element</u>	<u>Name</u>	
M	C186	QUANTITY DETAILS Quantity information in a transaction, qualified when relevant.	M
M	6063	Quantity qualifier Code giving specific meaning to a quantity. 12 Despatch quantity Quantity despatched by the seller.	M an..3
M	6060	Quantity Numeric value of a quantity.	M n..15
	6411	Measure unit qualifier Indication of the unit of measurement in which weight (mass), capacity, length, area, volume or other quantity is expressed. EA Each	C an..3

Group: **RFF** Segment Group 16: Reference
Position: 0710
Group: Segment Group 15 (Line Item) Conditional (Optional)
Level: 3
Usage: Conditional (Optional)
Max Use: 99
Purpose: A group of segments to give reference numbers and dates.

Segment Summary						
	Pos.	Seg.		Req.	Max.	Group:
	<u>No.</u>	<u>ID</u>	<u>Name</u>	<u>Des.</u>	<u>Use</u>	<u>Repeat</u>
M	0720	RFF	Reference	M	1	

Segment: **RFF** Reference
Position: 0720 (Trigger Segment)
Group: Segment Group 16 (Reference) Conditional (Optional)
Level: 3
Usage: Mandatory
Max Use: 1
Purpose: A segment identifying documents related to the line item.

Data Element Summary

	<u>Data Element</u>	<u>Component Element</u>	<u>Name</u>	<u>Attributes</u>
M	C506		REFERENCE	M
			Identification of a reference.	
M		1153	Reference qualifier	M an..3
			Code giving specific meaning to a reference segment or a reference number.	
		BM	Bill of lading number	
			Reference number assigned to a bill of lading, see: 1001 = 705.	
		SE	Serial number	
			Identification number of an item which distinguishes this specific item out of an number of identical items.	
		ZZZ	Mutually defined reference number	
			Number based on party agreement.	
		1154	Reference number	C an..35
			Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier.	
		1156	Line number	C an..6
			Number of the line in the document/message referenced in 1154 Reference number.	

Segment: **UNT** Message Trailer
Position: 1040
Group:
Level: 0
Usage: Mandatory
Max Use: 1
Purpose: A service segment ending a message, giving the total number of segments in the message and the control reference number of the message.

Data Element Summary

	Data	Component		
	<u>Element</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	0074		NUMBER OF SEGMENTS IN A MESSAGE Control count of number of segments in a message.	M n..6
M	0062		MESSAGE REFERENCE NUMBER Unique message reference assigned by the sender.	M an..14